

**SWIVEL CLIP ON NOZZLES**

SB series swivel clamps are specially designed swivel clip on nozzles with 'O' ring for maximum sealing. To install SB series swivel nozzle assembly on pipes all you need is drill a hole of 14 mm or 18 mm (selecting the model), insert the nozzle body inside and clamp it. This easy to install, adjust and service design and it is designed for modern surface pre-treatment plants. They provide excellent performance and easy maintenance.

Typical application : Used in pre-treatment process, industrial washing Machines and various processes.

Max working temperature : 80°C

Swivel Degree : 40°

Recommended working pressure : Single spring : 3 bar  
Double spring : 5 bar

**Materials**

Body : Polypropylene (20% - 25% glass filled)  
Clamp : SS 304 / SS 316 (optional)  
O-ring : (NBR) Nitrile Rubber, (FKM) Viton® (optional)

**Single Clamp****Double Clamp**

CODE		PIPE SIZE (inch)	PIPE OD (mm)	SUITABLE HOLE DIA (mm)
Single Clamp	Double Clamp			
SBE14	SBE24	3/4"	26.7	14
SBF14	SBF24	1"	33.4	14
SBG14	SBG24	1 1/4"	42.2	14
SBH14	SBH24	1 1/2"	48.3	14
SBK14	SBK24	2"	60.3	14
SBE16	SBE26	3/4"	26.7	16
SBF16	SBF26	1"	33.4	16
SBG16	SBG26	1 1/4"	42.2	16
SBH16	SBH26	1 1/2"	48.3	16
SBK16	SBK26	2"	60.3	16
SBE18	SBE28	3/4"	26.7	18
SBF18	SBF28	1"	33.4	18
SBG18	SBG28	1 1/4"	42.2	18
SBH18	SBH28	1 1/2"	48.3	18
SBK18	SBK28	2"	60.3	18