

EA Self-Rotating Spray Nozzles Stainless Steel & Plastic Versions











EA series nozzles are very compact and designed for cleaning process in small bore or small size of containers. The rotary motion allows it to clean the vessels effectively. It is available in all grade of stainless steel material and also available in plastics like PTFE along with several spray angles.

Coverage Type	Spray Angle					
B	180°					
	270°					
E	360°					

MODEL NO.	SPRAY ANGLE	CO	NNECT	ION	FLOW CAPACITY IN LPM AT DIFFERENT PRESSURE				CONNECTION	G/A DIMENSION. MM						
	S A				PRESSURE [BAR]					NOS						
		1/4"	3/8"	1/2"							MALE			FEMALE		
					1.5		3		7		Н	D	A/F	Н	D	A/F
EA2.100	B/D/E	•			8.66	10.00	12.25	15.81	18.71	1/4"	45	16	12.8	45	16	16
EA2.120	B/D/E	•	•		10.39	12.00	14.70	18.97	22.45	Weight (Metals) = XX gms. Approx						
EA2.150	B/D/E		•		12.99	15.00	18.37	23.72	28.06	3/8"	45	22.2	12.8	51	22.2	22
EA2.180	B/D/E		•		15.59	18.00	22.05	28.46	33.67	Weight (Metals) = 30.0 gms. Approx						
EA2.220	B/D/E		•	•	19.05	22.00	26.94	34.79	41.16	1/2"	79	30	22	79	30	24
EA2.300	B/D/E			•	25.98	30.00	36.74	47.43	56.12	Weight (Metals) = XX gms. Approx						
EA2.350	B/D/E			•	30.31	35.00	42.87	55.34	65.48							
EA2.400	B/D/E			•	34.64	40.00	48.99	63.25	74.83							

End Connection : X – BSP, Y - BSPT, Z – NPT Available.

Female Connection On Request