

NEW DESIGN

SWIVEL CLIP ON NOZZLES

SA series swivel clamps are specially designed swivel clip on nozzles. To install SA series swivel nozzle assembly on pipes all you need is drill a hole of 14 mm or 16 mm (selecting the model), insert the nozzle body inside and clamp it. This is a robust, easy to install, adjust and service design and it is designed for modern surface pre-treatment plants. They provide excellent performance and easy maintenance.

Typical application : Used in pre-treatment process, industrial washing Machines and various processes.

Max working temperature : 80°C

Swivel Degree : 40°


Recommended working pressure : Single spring : 3 bar
Double spring : 5 bar

Materials

Body : Polypropylene (20% - 25% glass filled)
Clamp : SS 304 / SS 316 (optional)
O-ring : (NBR) Nitrile Rubber, (FKM) Viton® (optional)



Single Clamp



Double Clamp

CODE		PIPE SIZE (inch)	PIPE OD (mm)	SUITABLE HOLE DIA (mm)
Single Clamp	Double Clamp			
SAE14	SAE24	3/4"	26.7	14
SAF14	SAF24	1"	33.4	14
SAG14	SAG24	1 1/4"	42.2	14
SAH14	SAH24	1 1/2"	48.3	14
SAK14	SAK26	2"	60.3	14
SAE16	SAE26	3/4"	26.7	16
SAF16	SAF26	1"	33.4	16
SAG16	SAG26	1 1/4"	42.2	16
SAH16	SAH26	1 1/2"	48.3	16
SAK16	SAK26	2"	60.3	16